

# PDCH-G15 Housing

For Canon Powershot G15 digital camera



The latest series of Canon G9, 10, 11, 12 housing.

Bulkhead and fiber-optic cable synchronization are available.

All functions of G15 camera are available in underwater.



The product is designed to operate easily in underwater and it provides comfortable shooting position.



67mm mount, wide angle and close-up conversion lenses are compatible(purchase 28mm lens for wide conversion).



Nikonos type 5pin, Patima type 6pin(choice)

Nikonos type 5pin and Patima type 6pin bulkheads are available.



Two fiber-optic cable adaptors

Two fiber-optic cable adaptors are installed for slave operation of two strobes.



Install the Patima accessory shoe joint(F, S type) on the built-in accessory shoe of the housing to use various accessories and target lights.



PL33 underwater video light(90° beaming angle, target lighting and video lighting purposes)



Single tray package



Double tray package

The exclusive tray for PDCH G9, 10, 11, 12, 15 housings is designed to connect aluminum arms and flexible arm system.



Buoyancy arm(S) 80g

Buoyancy arm(L) positive 320g



Flexible arm package



200mm arm



Standard joint



Cramp

## PDCH-G15 Housing specifications

1. Compatible device : Canon PowerShot G15 digital camera
2. Material : marine grade aluminum
3. Manufacturing : CNC machining
4. Surface treatment : anodized after barrel, sanding processes
5. Bulkhead connection : Patima type 6pin bulkhead, Nikonos type  
5pin bulkhead(option)
6. Slave synchronization : fiber-optic cable adaptor x 2
7. Port : 67mm mount, optical glass
8. Depth rating : 120m
9. Dimensions : 150 x 125 x 80mm (exclude the port)
10. Weight : 1,200g on land